


50
JAHRE
YEARS

THREE SIDE TIPPER

Two Side Tipper and low bed trailer



Sturdy Design.
Longevity.
Individuality.



Blomenröhr

We offer innovative transport solutions!

■ Innovative trailers for many purposes "Made in Germany"

For 50 years now Blumenröhr provides building contractors, forwarding agents, landscape gardeners, communities and recycling enterprises with innovative trailer technique. The tandem-low bed trailers, three- and two-side tippers and mini-semitrailers with particularly low loading height are the ideal transport aides for machinery and bulk material. Blumenröhr guarantees long-life products with high quality. Exclusively high-quality material and components of well-known manufacturers are used as well as all components of the vehicles are manufactured within the Blumenröhr plants with skilled workers. Blumenröhr can claim rightly that the products are "made in Germany". Because of the high manufacturing depth and the long experience the family run company can competently realise individual requirements.



■ Our strength: special equipment and attachments

Our trailers are an important part of your fleet management. They will save you money in transporting machinery and goods because they are well designed and equipped. We can offer a multitude of extra fittings and bespoke equipment. For instance, we design ramps for easy access; fitted sidewalls in lightweight aluminum; grids for the transportation of loose material; special lashing possibilities; various tool boxes; hydraulic ramp lifters and lots more. In addition, we can offer combined designs such as twin side tippers; combination trailers for transporting containers and low bed trailers, fitted with spaces underneath the floor for the loading of scaffolding. Come and discuss your requirements with us and we will ensure your purchase suits your needs!



■ Product Range

- Small low bed trailers up to 3,5 tons
- Low bed trailers 5,0 to -10,5 tons
- Three-side-tippers 5,0 to - 18 tons
- Two-side-tippers 10,5 to - 18 tons
- Mini-semitrailers

THREE SIDE TIPPER



Total weight 5000 kg, order number 845/5000, net load approx. 3100 kg, loading gauge approx. 4000x2300 mm, loading height unloaded approx. 850 mm, accessories: zink coated chassis, tool box



Total weight 6900 kg, order number 852/6900, net load approx. 4650 kg, loading gauge approx. 4000x2300 mm, loading height unloaded approx. 880 mm, accessories: tool box, warning stripe, hooks



Total weight 8900 kg, order number 863/8900, net load approx. 6450 kg, loading gauge approx. 4500x2300 mm, loading height unloaded approx. 880 mm, accessories: shelf for bucket



Total weight 10500 kg, order number 885/10500, net load approx. 7800 kg, loading gauge approx. 4500x2300 mm, alternatively 4500x2420 mm, loading height unloaded approx. 930 mm
Total weight 11900 kg, order number 884/11900, NL ap.9200 kg,



Total weight 14000 kg, order number 888/14000, net load approx. 10850 kg, loading gauge approx. 4500x2420 mm, loading height unloaded approx. 1100 mm, single tired (four tires)
Total weight 14000 kg, order number 887/14000 twin tired



Total weight 18000 kg, order number 889/18000, net load approx. 13800 kg, loading gauge approx. 5000x2420 mm, loading height unloaded approx. 1110 mm, twin tired (eight tires) accessories: feather jack and central locking

Easy and safe handling



Benefits at a glance

The tipper is equipped with a multi-step cylinder and a lift limiter - a guarantee for secure handling.

The drawbar is continuously adjustable by a winch (Range approx 0,72-1,02m). The winch is covered and protected by a strong steel frame.

Components of brand names are used - a guarantee for quality and a quick supply of spare parts.

The low loading height supports the quick and secure loading of machines.

The upper body is marked by short gaps of the crossbars, especially around the cylinder

The back ist equipped with two parking supports. The lamps are securely mounted.

The aluminium ramps can be sandwiched under the loading area. They are on rolls and can be easily withdrawn. The ramps can be plugged into the back and are secured against sliding. They can be used for tracked vehicles.

The ramps are secured against theft with a steel cap which can be locked.



IN PRACTICE

In Practice



TWO SIDE TIPPER

Two side tipper an low bed trailer

The tandem two side tipper and low bed trailer offers a very special solution: the loading ramps remain in vertical position during tipping. This transport solution from Blumenröhr allows due to the very low loading height, a simple loading and unloading. The sideways adjustable loading ramps are equipped with an adjustable spring supported jack and can simply be retracted by one hand. Also for long vehicles, the engine hydraulic tipping equipment with two tipping cylinders with stroke limiter, guarantees a steep tipping angle. The length of the loading floor can be up to 7 meters. Bulk goods are quickly and efficiently tipped of – also in case of an uneven load distribution.



Blomenröhr Fahrzeugbau GmbH

Schneidweg 31 • 59590 Geseke


Deutschland/Germany

Telefon: 0049-(0)2942-5799770

Fax: 0049-(0)2942-5799777

E-mail: info@blomenroehr.com

www.blomenroehr.com



Blomenröhr

WIR LÖSEN IHR TRANSPORTPROBLEM!